

OK Fencing Systems

Designed and Manufactured in Australia



OKA Post / Picket

Function: Live stock, exclusion and conservation. Barb wire fencing, lane ways and boundaries

Material: High tensile steel, with flex and return for wildlife or stock impact

Coating: GALFAN Coating 5% Aluminium, Rare Metals, Magnesium, 95% Zinc, the ultimate in corrosive resistant coating

Thickness: 1.8mm thick

Width: 86mm wide post/picket

Length: 1.65m (5.4ft), 1.8m (6ft), 2.1m (7ft), 2.4m (8ft), 2.7m (8.8ft)

Insert Depth Options: 585mm, 735mm

Wire Holes: Available in 75mm wire hole spacings, suitable for multiple mesh spacing

Special Features:

- Easy to load wire slots for twitching - 300mm x 2.5mm thick
- Internal wire slots are rounded to reduce wire wear
- The profile enhances strength and rigidity in the ground



OK products are carbon offset at manufacturing



Sales Enquiries: +61 (0) 488 662 562 | Nigel Catt: nigel@ocloc.com.au

www.OCAG.com.au

OCAG OK

Ocloc Kakadu OKA fence post/picket - 75mm wire slot spacings

Function: Stock control, laneways, internal & exclusion

Coating: GALFAN Coating - rare metals, aluminium, magnesium, zinc

Wire Slots 75mm spacings: Suits all mesh profiles + **top wire/ barb slots 17mm from the top** (included in the tabled slot numbers)

Material: High tensile steel, with flex

Thickness: 1.8mm thick

Width: 86mm wide

Length: 1.65m (5.4ft), 1.8m (6ft), 2.1m (7ft), 2.4m (8ft), 2.7m (8.8ft)



Insert Depth: 585mm

Twich Wire: 2.5mm


Strength: High tensile steel




585mm
Insert Depth




Wire slots



Ground level view bottom wire hole



Pointed tip for easy ramming



OKA order codes	OKA1.65(585)	OKA1.8(585)	OKA2.1(585)	OKA2.4(585)	OKA2.7(585)
OKA lengths	1.65m 5.4ft	1.8m 6ft	2.1m 7ft	2.4m 8ft	2.7m 8.8ft
Wire hole numbers at spacings 75mm	15	17	21	25	27

OK products are carbon offset at manufacturing



OK Fencing Systems

Designed and Manufactured in Australia

Ocloc Kakadu OKA fence post/picket - 75mm wire slot spacings

Function: Stock control, laneways, internal & exclusion

Coating: GALFAN Coating - rare metals, aluminium, magnesium, zinc

Wire Slots 75mm spacings: Suits all mesh profiles + **top wire/ barb slots 17mm from the top** (included in the tabled slot numbers)

Material: High tensile steel, with flex

Thickness: 1.8mm thick

Width: 86mm wide

Length: 1.65m (5.4ft), 1.8m (6ft), 2.1m (7ft), 2.4m (8ft), 2.7m (8.8ft)



Insert Depth: 735mm

Twich Wire: 2.5mm


Strength: High tensile steel




735mm
Insert Depth




Wire slots



Ground level view bottom wire hole



Pointed tip for easy ramming



OKA order codes	OKA2.1(735)	OKA2.4(735)
OKA lengths	2.1m 7ft	2.4m 8ft
Wire hole numbers at spacings 75mm	21	25

OK products are carbon offset at manufacturing



Sales Enquiries: +61 (0) 488 662 562 | Nigel Catt: nigel@ocloc.com.au

www.OCAG.com.au

OCAG OK