

OK Fencing Systems

Designed and Manufactured in Australia



OKY Post / Picket

Function: Live stock, exclusion and conservation. Barb wire fencing, lane ways and boundaries.

Material: High tensile steel, with flex and return for wildlife or stock impact

Coating: GALFAN Coating 5% Aluminium, Rare Metals, Magnesium, 95% Zinc, the ultimate in corrosive resistant coating

Thickness: 1.8mm thick

Width: 86mm wide post/picket

Length: 1.65m (5.4ft), 1.8m (6ft), 2.1m (7ft), 2.4m (8ft)

Insert Depth Options: 585mm, 735mm

Wire Holes: Available in 75mm wire hole spacings, suitable for multiple mesh spacing

Special Features:

- Easy to load wire slots for twitching - 300mm x 2.5mm thick
- Internal wire slots are rounded to reduce wire wear
- The profile enhances strength and rigidity in the ground
- **Designed and manufactured in Australia**



OK products are carbon offset at manufacturing — Australian designed & manufactured



Sales Enquiries: +61 (0) 488 662 562 | Nigel Catt: nigel@ocloc.com.au

www.ocloc.com.au

OCAG OK

OK Fencing Systems

Designed and Manufactured in Australia

Ocloc Kakadu OKY fence post/picket - 75mm wire slot spacings

Function: Stock control, laneways, internal & exclusion

Coating: GALFAN Coating - rare metals, aluminium, magnesium, zinc

Wire Slots: **75mm spacings** - suits all mesh profiles + **top wire/barb wire slot 17mm from the top** (included in the tabled slot numbers)

Material: High tensile steel, with flex

Thickness: **1.8mm thick**

Width: 86mm wide

Length: **1.65m** (5.4ft), **1.8m** (6ft), **2.1m** (7ft), **2.4m** (8ft)




Insert Depth: **585mm**

Twich Wire: 2.5mm



Strength: High tensile steel



585mm
Insert Depth



Ground level view bottom wire hole



OKY order codes	OKB1.65(585)	OKB1.8(585)	OKB2.1(585)	OKB2.4(585)
OKY lengths	1.65m 5.4ft	1.8m 6ft	2.1m 7ft	2.4m 8ft
Wire hole numbers at spacings 75mm	15	17	21	25

OK products are carbon offset at manufacturing — Australian designed & manufactured



Sales Enquiries: +61 (0) 488 662 562 | Nigel Catt: nigel@ocloc.com.au

www.ocloc.com.au

OCAG OK

OK Fencing Systems

Designed and Manufactured in Australia

Ocloc Kakadu OKY fence post/picket - 75mm wire slot spacings

Function: Stock control, laneways, internal & exclusion

Coating: GALFAN Coating - rare metals, aluminium, magnesium, zinc

Wire Slots: **75mm spacings** - suits all mesh profiles + **top wire/barb wire slot 17mm from the top** (included in the tabled slot numbers)

Material: High tensile steel, with flex

Thickness: **1.8mm thick**

Width: 86mm wide

Length: **2.1m** (7ft), **2.4m** (8ft)






Insert Depth: **735mm**

Twist Wire: 2.5mm

Strength: High tensile steel



735mm
Insert Depth



OKY order codes	OKB2.1(735)	OKB2.4(735)
OKY lengths	2.1m 7ft	2.4m 8ft
Wire hole numbers at spacings 75mm	21	25

OK products are carbon offset at manufacturing — Australian designed & manufactured



Sales Enquiries: +61 (0) 488 662 562 | Nigel Catt: nigel@ocloc.com.au

www.ocloc.com.au

OCAG OK